A-98
Alere Corp
1 1/29/81

213-222
577-881

...ed and installed in the ...s that wallboard panels ...ace from floor to ceiling ..., as required.

...titions shall be ...e bearing ...ation and N.Y.C. ...alendar numbers.

...e roll formed ...of U.S.S. No. 25 ...rs shall be in

...d of U.S.S. No. 25 ...all include corner ... edge trim.

... complete with ...hall be type No. 11 ...d by U.S. Gypsum Co., ... and edge trim members

...d to studs shall be ...e specifically ...installation.

...ll be expressly ...manufacturer for use ...ed materials. Joint ...xed type conforming ...nt shall be perforated ... Taping and spackling ...ation.

...ing top of stud with ... from metal ...ypsum wallboard to

... tightly packed in ... fire rated partitions ...ished. Thermatiber ... manufactured by U.S.

... be one of the following:

...-Aire

... by Davoe & Reynolds, ...qual.

...ecifically manufactured ... which it is to be

Walls shall have two (2) coats of paint. Doors and frames shall have two (2) coats of paint both sides, unless otherwise noted. PAINT ALL WALLS AS PER FINISH SCHEDULE.

Ceiling Tile shall be painted, one coat Luminall satin paint, ACRYLOVRENE No. 21801 White, as manufactured by Luminall Paint Company or approved equal. All tile should be dropped and painted off grid.

PAINT DOORS, FRAMES AND CONVECTORS AS PER FINISH SCHEDULE.

WALL COVERING

Prime and seal all surfaces scheduled for wall covering as per finish schedule.

All work shall be in accordance with the manufacturer's printed instructions.

Closet Shelf and Clothes Pole

Closet shelf shall be 3/4" thick particle board supported by continuous angle on three sides. Paint shelf and angle to match walls. Clothes pole shall be 1" O.D. 20 Ga. chrome plated steel tubing No. T800 as manufactured by Plaza Towel Holder Co. or approved equal.

MATERIALS FURNISHED BY THE AUTHORITY

The authority will furnish to the contractor the materials in the quantities as shown below for installation in the permanent construction. The furnishing and installation of any materials in addition to the quantities shown shall be the responsibility of the contractor.

Materials can be obtained at Tower B basement level 294. Material storage area is open daily from 7:30 a.m. - 12:00 noon and 1:00 p.m. - 3:30 p.m. For material withdrawals, call (212) 466-4154 at least 24 hours in advance.

All excess material furnished by the Authority not used in the permanent construction shall be returned as directed by PA ENGINEER. (2)

All components for ~~a movable~~ gypsum wallboard partition (2) 72 L.F.

Ceiling and floor runners for salvaged (movable gypsum wallboard) partition 0 L.F.

Vinyl asbestos floor tile 0 S.F.

Wall Base
(a) Straight 44 L.F.
(b) Cove 0 L.F.

Set III 1 (2) pairs butts, (1) latchset, (1) domestop, (3) silencers

Set III 5 (2) pairs butts, (1) latchset, (1) domestop, (3) silencers

Set IV 2 (4) pairs butts, (2) domestops, (1) latchset, (2) silencers

Aluminum Saddles: 3'-0" 1 ~~[illegible]~~

Hollow metal doors and frames

Door	Description	Hdwr. Set
1	3'0"x8'-5¾" INTERIOR	III
2	" " " "	III
3	" " " "	II
4	(2) 2'0"x8'-5¾" INTERIOR	IV
5	3'0"x8'-5¾" FIRE/ENTRY	I

INSTALLATION OF MATERIALS

MOVABLE GYPSUM WALLBOARD PARTITIONS

The installation of movable gypsum wallboard partitions shall be in accordance with currently printed manufacturers instructions and recommendations unless otherwise directed by RCL/Design Group Inc.

HARDWARE

Finish hardware installation shall conform to the manufacturers requirements. Installation shall be in a neat and skillful manner, with all components operating properly. All knobs, handles, pulls and other exposed items, shall be suitably wrapped and protected as soon as they have been installed and such protection shall shall remain until the acceptance of the work.

Immediately preceding final inspection all hardware shall be cleaned carefully so as not to damage it.

Butts - Stanley FBB 179 X [illegible]
Mortise Lockset - Corbin [illegible]
Latch Set - Corbin #82[illegible]
Closer - Corbin #[illegible]
Flush Bolts - Corbin #284[illegible] lg., 1'-10" lg.
Domestop - Corbin #273-1/2
Coordinator - Von Duprin [illegible]
Silencers - Corbin #[illegible]
Aluminum Saddles - Zero Weatherstripping Co., Inc. #[illegible]

After erection, all damaged ... exposed surfaces of bolts, washers, and all field welds ... painted areas adjacent ... with the same paint ...

WALL BASE

Wall base shall be applied ... approved type cement adhesive below top of base. Adhesive ... base shall be furnished by ... joints shall be held to a ... distance from a joint to a ...

ACOUSTIC CEILING

Black iron carrying channels supported by hangers fastened ... structural members, channels ... required to adequately support ... drapery pocket and the acoustic ...

Ceiling tile shall be installed ... even plane, butt joints tight ... metal edge mouldings as required ...

MODIFY ACOUSTIC CEILING AS ... LAYOUT AS SHOWN ON REFLECTED ...

NOTES

1. The work required under ... be performed on (STA ... otherwise required by ... contractor as directed by ... Inc. and The World Trade ...

2. Before commencing ... verify all conditions ... field. Any errors ... brought to the attention ... Inc. and the World Trade ...

3. Before commencing work ... notify RCL/Design Group ... Trade Center of any areas ... All exposed structural members ... of fireproofing shall be ... with CARCO D-C/F ... directed by RCL/Design ... World Trade Center.

4. The contractor shall ... existing ... approval ... and The World Trade Center.

5. The Contractor shall ... tenant space below ... from floor drilling ...

6. The Contractor shall ... construction damaged ... Contract.

SPECIFICATIONS

RCL DESIGN GROUP INC.
100 BRICKSTONE MINEOLA, N.Y. 11501 516/746-1567

designed by
drawn by
date
revised
revised
revised

REVERSE DWG

BEST COPY AVAILABLE